




NPV132-9-695BN

- **132 CELL**
Mono TOPCON Module
- **1500VDC**
Maximum System Voltage
- **675-695Wp**
Power Output Range
- **22.4%**
Maximum Efficiency




KEY SALIENT FEATURES

- Global, bankable brand, with independently certified state-of-the-art automated manufacturing
- Industry leading lowest thermal co-efficient of power
- Industry leading 12 years product warranty
- Excellent low irradiance performance
- Excellent PID resistance
- Positive power tolerance of 0~+3%
- Dual stage 100% EL Inspection warranting defect-free product
- Module Imp binning radically reduces string mismatch losses
- Excellent wind load 2400Pa & snow load 5400Pa under certain installation method
- Comprehensive product and system certification
 - ◆ IEC61215:2016; IEC61730-1/-2:2016;
 - ◆ ISO 9001:2015 Quality Management System
 - ◆ ISO 14001:2015 Environmental Management System
 - ◆ ISO 45001:2018 Occupational Health and Safety Management System

HIGH PERFORMANCE N-TYPE TOPCON MONOCRYSTALLINE MODULE


LINEAR PERFORMANCE WARRANTY

12 year Product Warranty / 25 year Linear Power Warranty



★ Please check the valid version of Limited Product Warranty which is officially released by NanoPV

Dimensions of PV Module Unit: mm



ELECTRICAL DATA (STC)

Model Number	NPV132-9-675BN	NPV132-9-680BN	NPV132-9-685BN	NPV132-9-690BN	NPV132-9-695BN
Rated Power in Watts-Pmax(Wp)	675	680	685	690	695
Open Circuit Voltage-Voc(V)	47.36	47.55	47.74	47.93	48.12
Short Circuit Current-Isc(A)	17.96	18.02	18.08	18.14	18.20
Maximum Power Voltage-Vmpp(V)	39.52	39.70	39.88	40.06	40.24
Maximum Power Current-Impp(A)	17.09	17.14	17.18	17.22	17.27
Module Efficiency (%)	21.7	21.9	22.1	22.2	22.4

STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.
 ★ Module Efficiency (%): Round-off to the nearest number

ELECTRICAL DATA (NMOT)

Model Number	NPV132-9-675BN	NPV132-9-680BN	NPV132-9-685BN	NPV132-9-690BN	NPV132-9-695BN
Rated Power in Watts-Pmax(Wp)	511.3	515.1	518.7	522.2	526.1
Open Circuit Voltage-Voc(V)	44.05	44.22	44.40	44.58	44.75
Short Circuit Current-Isc(A)	14.73	14.78	14.83	14.88	14.93
Maximum Power Voltage-Vmpp(V)	36.67	36.84	37.01	37.18	37.34
Maximum Power Current-Impp(A)	13.94	13.98	14.02	14.05	14.09

NMOT: Irradiance at 800 W/m², Ambient Temperature 20°C, Wind Speed 1 m/s.

MECHANICAL DATA

Solar cells	N-TYPE TOPCON Monocrystalline
Cell configuration	132 cells (6×11+6×11)
Module dimensions	2384×1303×35mm
Weight	33.5kg
Superstrate	High Transmission, Low Iron, Tempered ARC Glass
Substrate	White Back-sheet
Frame	Anodized Aluminium Alloy, Silver Color
J-Box	Potted, IP68, 1500VDC, 3 Schottky bypass diodes
Cables	4.0mm ² , Positive(+)350mm, Negative(-)230mm (Connector Included)
Connector	IP68

TEMPERATURE & MAXIMUM RATINGS

Nominal Module Operating Temperature (NMOT)	44°C±2°C
Temperature Coefficient of Voc	-0.25%/°C
Temperature Coefficient of Isc	0.04%/°C
Temperature Coefficient of Pmax	-0.34%/°C
Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500VDC
Max Series Fuse Rating	30A
Limiting Reverse Current	30A

PACKAGING CONFIGURATION

	40ft(HQ)
Number of modules per container	558
Number of modules per pallet	31
Number of pallets per container	18
Packaging box dimensions (LxWxH) in mm	1320×1120×2515
Box gross weight[kg]	1090

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.
 ©2023 NanopV. All rights reserved. Contents included in this datasheet are subject to change without notice.
 No special undertaking or warranty for the suitability of special purpose or being installed in extraordinary surroundings is granted unless as otherwise specifically committed by manufacturer in contract document.

Contact US:

NanoPV Solar Inc.,
 103 Carnegie Center Dr.,
 Princeton,
 New Jersey - 08540,
 USA.
Email: info@nano-pv.com
Website: www.nano-pv.com

